

HMMKP82

双面金属化聚丙烯膜电容器




特点

- 负电容量温度系数
- 双面金属化作为电极
- 产品损耗小，内部温升小
- 优异的阻燃性能

主要用途

- 广泛应用于高频、高压、脉冲和谐振电路中

外形示意图



技术要求

引用标注	GB/T10190(IEC60384-16)					
气候类别	40/105/56					
工作温度范围	-40°C~105°C +75°C~+105°C: 温度每升高 1°C 额定电压降低 1.35%, 对于额定电压 U_R (a.c.) +85°C~+105°C: 温度每升高 1°C 额定电压降低 1.25%, 对于额定电压 U_R (d.c.)					
额定温度	85°C for U_R (dc), 75°C for U_R (ac)					
额定电压	250Vdc/180Vac、400Vdc/250Vac、630Vdc/400Vac、 1000Vdc/600Vac、1600Vdc/650Vac、2000Vdc/700Vac					
电容量范围	0.00068 μ F~3.9 μ F					
电容量偏差	$\pm 5\%$ (J)、 $\pm 10\%$ (K)、 $\pm 20\%$ (M) (20°C $\pm 5^\circ$ C, 1kHz)					
耐电压	1.6 U_R (5s)					
损耗角正切	≤ 0.0010 (1kHz, 20°C)					
绝缘电阻 ($IR \times C_N$)	R $\geq 100000M\Omega$ $C_N \leq 0.33\mu F$ R $C_N \geq 30000s$ $C_N > 0.33\mu F$		(20°C, 100Vd.c, 1min)			
最大脉冲爬升速率: 若实际工 作电 压 U 比额定电压 U_R 低, 电容器可工 作在更高的 dV/dt 场合, 这样 dV/dt 允许值应为右表值乘以 U_R/U	U_R (V)	dV/dt(V/ μ s)				
		P=7.5	P=10.0	P=15.0	P=22.5	P=27.5
	250	1200	1000	550	250	200
	400	1800	1500	900	500	300
	630	3200	3200	2500	1500	900
	1000	6000	6000	3300	2100	1000
	1600	—	8000	5500	3000	2000
2000	—	—	7500	4200	2200	

产品订货标记说明

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
H	M	M	K	P	8	2	/	3	A	2	2	4	J	6	0					(x	x	x)
电容器代码								直流额定 电压代码		标称容量 代码			容量偏差 代码	引线脚距/ 外形尺寸	内部 特征码	引出端 代码			内部特征码					
								2E=250V 2G=400V 2J=630V 3A=1000V 3C=1600V 3D=2000V		举例: 334=33 $\times 10^4$ pF =0.33 μ F			K= $\pm 10\%$ J= $\pm 5\%$	3=7.5mm 4=10mm 6=15mm 9=22.5mm B=27.5mm	0 (普通品) 见表1 其他数字 (特征码)			内部特征码						

表1: 引出端代码

第 16 位		第 17 位		第 18 位		第 19 位	
代码	说明	代码	说明	代码	说明	代码	说明
A	编带包装	3	P=7.5mm	0	表示直脚	1	产品在连续的两个载孔带之间
		4	P=10.0mm			5	产品在连续的两个载孔带之间
		6	P=15.0mm				
C	直脚	00	标准的引线长度 (18mm~28mm)			0	引线长度偏差±0.5mm 或标准长度
		35	引线长度 3.5mm				

产品尺寸

250Vdc (180Vac)													
C _R (μF)	W mm	H mm	T mm	P mm	D mm	产品订货标记	C _R (μF)	W mm	H mm	T mm	P mm	D mm	产品订货标记
0.068	18.0	11.0	5.0	15.0	0.8	HMMKP82/2E683-60****	0.47	26.0	16.0	7.0	22.5	0.8	HMMKP82/2E474-90****
0.082	18.0	11.0	5.0	15.0	0.8	HMMKP82/2E823-60****	0.56	26.0	17.0	8.5	22.5	0.8	HMMKP82/2E564-90****
0.10	18.0	11.0	5.0	15.0	0.8	HMMKP82/2E104-60****	0.68	26.0	19.0	10.0	22.5	0.8	HMMKP82/2E684-90****
0.12	18.0	12.0	6.0	15.0	0.8	HMMKP82/2E124-60****	0.82	26.0	19.0	10.0	22.5	0.8	HMMKP82/2E824-90****
0.15	18.0	12.0	6.0	15.0	0.8	HMMKP82/2E154-60****	1.0	26.0	22.0	12.0	22.5	0.8	HMMKP82/2E105-90****
0.18	18.0	13.5	7.5	15.0	0.8	HMMKP82/2E184-60****	0.68	32.0	18.0	9.0	27.5	0.8	HMMKP82/2E684-B0****
0.22	18.0	13.5	7.5	15.0	0.8	HMMKP82/2E224-60****	0.82	32.0	18.0	9.0	27.5	0.8	HMMKP82/2E824-B0****
0.27	18.0	14.5	8.5	15.0	0.8	HMMKP82/2E274-60****	1.0	32.0	20.0	11.0	27.5	0.8	HMMKP82/2E105-B0****
0.33	18.0	16.0	10.0	15.0	0.8	HMMKP82/2E334-60****	1.2	32.0	20.0	11.0	27.5	0.8	HMMKP82/2E125-B0****
0.39	18.0	16.0	10.0	15.0	0.8	HMMKP82/2E394-60****	1.5	32.0	22.0	13.0	27.5	0.8	HMMKP82/2E155-B0****
0.47	18.0	19.0	11.0	15.0	0.8	HMMKP82/2E474-60****	1.8	32.0	24.5	15.0	27.5	0.8	HMMKP82/2E185-B0****
0.18	26.0	15.0	6.0	22.5	0.8	HMMKP82/2E184-90****	2.2	32.0	28.0	14.0	27.5	0.8	HMMKP82/2E225-B0****
0.22	26.0	15.0	6.0	22.5	0.8	HMMKP82/2E224-90****	2.7	32.0	33.0	18.0	27.5	0.8	HMMKP82/2E275-B0****
0.27	26.0	15.0	6.0	22.5	0.8	HMMKP82/2E274-90****	3.3	32.0	33.0	18.0	27.5	0.8	HMMKP82/2E335-B0****
0.33	26.0	15.0	6.0	22.5	0.8	HMMKP82/2E334-90****	3.9	32.0	33.0	18.0	27.5	0.8	HMMKP82/2E395-B0****
0.39	26.0	16.0	7.0	22.5	0.8	HMMKP82/2E394-90****							

备注: (1)“-”表示容量等级, J=±5%, K=±10%, M=±20%。

(2)“****”表示引线加工和包装代码 (见表1)。

产品尺寸

400Vdc (250Vac)													
C _R (μF)	W mm	H mm	T mm	P mm	D mm	产品订货标记	C _R (μF)	W mm	H mm	T mm	P mm	D mm	产品订货标记
0.022	10.0	12.0	6.0	7.5	0.6	HMMKP82/2G223-30****	0.27	18.0	16.0	10.0	15.0	0.8	HMMKP82/2G274-60****
0.027	10.0	12.0	6.0	7.5	0.6	HMMKP82/2G273-30****	0.33	18.0	19.0	11.0	15.0	0.8	HMMKP82/2G334-60****
0.01	13.0	9.0	4.0	10.0	0.6	HMMKP82/2G103-40****	0.39	18.0	19.0	11.0	15.0	0.8	HMMKP82/2G394-60****
0.012	13.0	9.0	4.0	10.0	0.6	HMMKP82/2G123-40****	0.12	26.0	15.0	6.0	22.5	0.8	HMMKP82/2G124-90****
0.015	13.0	9.0	4.0	10.0	0.6	HMMKP82/2G153-40****	0.15	26.0	15.0	6.0	22.5	0.8	HMMKP82/2G154-90****
0.018	13.0	9.0	4.0	10.0	0.6	HMMKP82/2G183-40****	0.18	26.0	15.0	6.0	22.5	0.8	HMMKP82/2G184-90****
0.022	13.0	9.0	4.0	10.0	0.6	HMMKP82/2G223-40****	0.22	26.0	16.0	7.0	22.5	0.8	HMMKP82/2G224-90****
0.027	13.0	9.0	4.0	10.0	0.6	HMMKP82/2G273-40****	0.27	26.0	17.0	8.5	22.5	0.8	HMMKP82/2G274-90****
0.033	13.0	11.0	5.0	10.0	0.6	HMMKP82/2G333-40****	0.33	26.0	17.0	8.5	22.5	0.8	HMMKP82/2G334-90****
0.039	13.0	11.0	5.0	10.0	0.6	HMMKP82/2G393-40****	0.39	26.0	17.0	8.5	22.5	0.8	HMMKP82/2G394-90****
0.047	13.0	11.0	5.0	10.0	0.6	HMMKP82/2G473-40****	0.47	26.0	19.0	10.0	22.5	0.8	HMMKP82/2G474-90****
0.056	13.0	12.0	6.0	10.0	0.6	HMMKP82/2G563-40****	0.56	26.0	19.0	11.0	22.5	0.8	HMMKP82/2G564-90****
0.033	18.0	11.0	5.0	15.0	0.8	HMMKP82/2G333-60****	0.68	26.0	22.0	12.0	22.5	0.8	HMMKP82/2G684-90****
0.039	18.0	11.0	5.0	15.0	0.8	HMMKP82/2G393-60****	0.39	32.0	18.0	9.0	27.5	0.8	HMMKP82/2G394-B0****
0.047	18.0	11.0	5.0	15.0	0.8	HMMKP82/2G473-60****	0.47	32.0	18.0	9.0	27.5	0.8	HMMKP82/2G474-B0****
0.056	18.0	11.0	5.0	15.0	0.8	HMMKP82/2G563-60****	0.56	32.0	20.0	11.0	27.5	0.8	HMMKP82/2G564-B0****
0.068	18.0	11.0	5.0	15.0	0.8	HMMKP82/2G683-60****	0.68	32.0	20.0	11.0	27.5	0.8	HMMKP82/2G684-B0****
0.082	18.0	12.0	6.0	15.0	0.8	HMMKP82/2G823-60****	0.82	32.0	22.0	13.0	27.5	0.8	HMMKP82/2G824-B0****
0.10	18.0	12.0	6.0	15.0	0.8	HMMKP82/2G104-60****	1.0	32.0	22.0	13.0	27.5	0.8	HMMKP82/2G105-B0****
0.12	18.0	13.5	7.5	15.0	0.8	HMMKP82/2G124-60****	1.2	32.0	24.5	15.0	27.5	0.8	HMMKP82/2G125-B0****
0.15	18.0	13.5	7.5	15.0	0.8	HMMKP82/2G154-60****	1.5	32.0	24.5	15.0	27.5	0.8	HMMKP82/2G155-B0****
0.18	18.0	14.5	8.5	15.0	0.8	HMMKP82/2G184-60****	1.8	32.0	33.0	18.0	27.5	0.8	HMMKP82/2G185-B0****
0.22	18.0	16.0	10.0	15.0	0.8	HMMKP82/2G224-60****	2.2	32.0	33.0	18.0	27.5	0.8	HMMKP82/2G225-B0****
630Vdc (400Vac)													
C _R (μF)	W mm	H mm	T mm	P mm	D mm	产品订货标记	C _R (μF)	W mm	H mm	T mm	P mm	D mm	产品订货标记
0.0010	10.0	9.0	4.0	7.5	0.6	HMMKP82/2J102-30****	0.0018	10.0	9.0	4.0	7.5	0.6	HMMKP82/2J182-30****
0.0012	10.0	9.0	4.0	7.5	0.6	HMMKP82/2J122-30****	0.0022	10.0	9.0	4.0	7.5	0.6	HMMKP82/2J222-30****
0.0015	10.0	9.0	4.0	7.5	0.6	HMMKP82/2J152-30****	0.0027	10.0	9.0	4.0	7.5	0.6	HMMKP82/2J272-30****

备注: (1)“-”表示容量等级, J=±5%, K=±10%, M=±20%。

(2)“****”表示引线加工和包装代码(见表1)。

产品尺寸

630Vdc (400Vac)													
CR (μF)	W mm	H mm	T mm	P mm	D mm	产品订货标记	CR (μF)	W mm	H mm	T mm	P mm	D mm	产品订货标记
0.0033	10.0	9.0	4.0	7.5	0.6	HMMKP82/2J332-30****	0.082	18.0	14.5	8.5	15.0	0.8	HMMKP82/2J823-60****
0.0039	10.0	9.0	4.0	7.5	0.6	HMMKP82/2J392-30****	0.10	18.0	16.0	10.0	15.0	0.8	HMMKP82/2J104-60****
0.0047	10.0	9.0	4.0	7.5	0.6	HMMKP82/2J472-30****	0.12	18.0	19.0	11.0	15.0	0.8	HMMKP82/2J124-60****
0.0056	10.0	9.0	4.0	7.5	0.6	HMMKP82/2J562-30****	0.15	18.0	19.0	11.0	15.0	0.8	HMMKP82/2J154-60****
0.0068	10.0	11.0	5.0	7.5	0.6	HMMKP82/2J682-30****	0.047	26.0	15.0	6.0	22.5	0.8	HMMKP82/2J473-90****
0.0082	10.0	11.0	5.0	7.5	0.6	HMMKP82/2J822-30****	0.056	26.0	15.0	6.0	22.5	0.8	HMMKP82/2J563-90****
0.010	10.0	12.0	6.0	7.5	0.6	HMMKP82/2J103-30****	0.068	26.0	15.0	6.0	22.5	0.8	HMMKP82/2J683-90****
0.012	10.0	12.0	6.0	7.5	0.6	HMMKP82/2J123-30****	0.082	26.0	15.0	6.0	22.5	0.8	HMMKP82/2J823-90****
0.0039	13.0	9.0	4.0	10.0	0.6	HMMKP82/2J392-40****	0.10	26.0	15.0	6.0	22.5	0.8	HMMKP82/2J104-90****
0.0047	13.0	9.0	4.0	10.0	0.6	HMMKP82/2J472-40****	0.12	26.0	16.0	7.0	22.5	0.8	HMMKP82/2J124-90****
0.0056	13.0	9.0	4.0	10.0	0.6	HMMKP82/2J562-40****	0.15	26.0	17.0	8.5	22.5	0.8	HMMKP82/2J154-90****
0.0068	13.0	9.0	4.0	10.0	0.6	HMMKP82/2J682-40****	0.18	26.0	17.0	8.5	22.5	0.8	HMMKP82/2J184-90****
0.0082	13.0	9.0	4.0	10.0	0.6	HMMKP82/2J822-40****	0.22	26.0	19.0	10.0	22.5	0.8	HMMKP82/2J224-90****
0.010	13.0	11.0	5.0	10.0	0.6	HMMKP82/2J103-40****	0.27	26.0	20.0	11.0	22.5	0.8	HMMKP82/2J274-90****
0.012	13.0	11.0	5.0	10.0	0.6	HMMKP82/2J123-40****	0.33	26.0	22.0	12.0	22.5	0.8	HMMKP82/2J334-90****
0.015	13.0	11.0	5.0	10.0	0.6	HMMKP82/2J153-40****	0.39	26.0	22.0	12.0	22.5	0.8	HMMKP82/2J394-90****
0.018	13.0	12.0	6.0	10.0	0.6	HMMKP82/2J183-40****	0.15	32.0	18.0	9.0	27.5	0.8	HMMKP82/2J154-B0****
0.022	13.0	12.0	6.0	10.0	0.6	HMMKP82/2J223-40****	0.18	32.0	18.0	9.0	27.5	0.8	HMMKP82/2J184-B0****
0.012	18.0	11.0	5.0	15.0	0.8	HMMKP82/2J123-60****	0.22	32.0	18.0	9.0	27.5	0.8	HMMKP82/2J224-B0****
0.015	18.0	11.0	5.0	15.0	0.8	HMMKP82/2J153-60****	0.27	32.0	18.0	9.0	27.5	0.8	HMMKP82/2J274-B0****
0.018	18.0	11.0	5.0	15.0	0.8	HMMKP82/2J183-60****	0.33	32.0	20.0	11.0	27.5	0.8	HMMKP82/2J334-B0****
0.022	18.0	11.0	5.0	15.0	0.8	HMMKP82/2J223-60****	0.39	32.0	20.0	11.0	27.5	0.8	HMMKP82/2J394-B0****
0.027	18.0	11.0	5.0	15.0	0.8	HMMKP82/2J273-60****	0.47	32.0	22.0	13.0	27.5	0.8	HMMKP82/2J474-B0****
0.033	18.0	12.0	6.0	15.0	0.8	HMMKP82/2J333-60****	0.56	32.0	22.0	13.0	27.5	0.8	HMMKP82/2J564-B0****
0.039	18.0	12.0	6.0	15.0	0.8	HMMKP82/2J393-60****	0.68	32.0	24.5	15.0	27.5	0.8	HMMKP82/2J684-B0****
0.047	18.0	12.0	6.0	15.0	0.8	HMMKP82/2J473-60****	0.82	32.0	28.0	14.0	27.5	0.8	HMMKP82/2J824-B0****
0.056	18.0	13.0	7.0	15.0	0.8	HMMKP82/2J563-60****	1.0	32.0	33.0	18.0	27.5	0.8	HMMKP82/2J105-B0****
0.068	18.0	14.5	8.5	15.0	0.8	HMMKP82/2J683-60****	1.2	32.0	33.0	18.0	27.5	0.8	HMMKP82/2J125-B0****

备注: (1)“-”表示容量等级, J=±5%, K=±10%, M=±20%。

(2)“****”表示引线加工和包装代码(见表1)。

产品尺寸

1000Vdc (600Vac)													
C _R (μF)	W mm	H mm	T mm	P mm	D mm	产品订货标记	C _R (μF)	W mm	H mm	T mm	P mm	D mm	产品订货标记
0.00068	10.0	9.0	4.0	7.5	0.6	HMMKP82/3A681-30****	0.047	18.0	14.5	8.5	15.0	0.8	HMMKP82/3A473-60****
0.00082	10.0	9.0	4.0	7.5	0.6	HMMKP82/3A821-30****	0.056	18.0	16.0	10.0	15.0	0.8	HMMKP82/3A563-60****
0.0010	10.0	9.0	4.0	7.5	0.6	HMMKP82/3A102-30****	0.068	18.0	19.0	11.0	15.0	0.8	HMMKP82/3A683-60****
0.0012	10.0	9.0	4.0	7.5	0.6	HMMKP82/3A122-30****	0.082	18.0	19.0	11.0	15.0	0.8	HMMKP82/3A823-60****
0.0015	10.0	11.0	5.0	7.5	0.6	HMMKP82/3A152-30****	0.033	26.0	15.0	6.0	22.5	0.8	HMMKP82/3A333-90****
0.0018	10.0	11.0	5.0	7.5	0.6	HMMKP82/3A182-30****	0.039	26.0	15.0	6.0	22.5	0.8	HMMKP82/3A393-90****
0.0022	10.0	11.0	5.0	7.5	0.6	HMMKP82/3A222-30****	0.047	26.0	15.0	6.0	22.5	0.8	HMMKP82/3A473-90****
0.0027	10.0	12.0	6.0	7.5	0.6	HMMKP82/3A272-30****	0.056	26.0	16.0	7.0	22.5	0.8	HMMKP82/3A563-90****
0.0033	10.0	12.0	6.0	7.5	0.6	HMMKP82/3A332-30****	0.068	26.0	16.0	7.0	22.5	0.8	HMMKP82/3A683-90****
0.0039	10.0	12.0	6.0	7.5	0.6	HMMKP82/3A392-30****	0.082	26.0	17.0	8.5	22.5	0.8	HMMKP82/3A823-90****
0.0010	13.0	9.0	4.0	10.0	0.6	HMMKP82/3A102-40****	0.10	26.0	17.0	8.5	22.5	0.8	HMMKP82/3A104-90****
0.0012	13.0	9.0	4.0	10.0	0.6	HMMKP82/3A122-40****	0.12	26.0	19.0	10.0	22.5	0.8	HMMKP82/3A124-90****
0.0015	13.0	9.0	4.0	10.0	0.6	HMMKP82/3A152-40****	0.15	26.0	20.0	11.0	22.5	0.8	HMMKP82/3A154-90****
0.0018	13.0	9.0	4.0	10.0	0.6	HMMKP82/3A182-40****	0.18	26.0	22.0	12.0	22.5	0.8	HMMKP82/3A184-90****
0.0022	13.0	9.0	4.0	10.0	0.6	HMMKP82/3A222-40****	0.10	32.0	18.0	9.0	27.5	0.8	HMMKP82/3A104-B0****
0.0027	13.0	9.0	4.0	10.0	0.6	HMMKP82/3A272-40****	0.12	32.0	20.0	11.0	27.5	0.8	HMMKP82/3A124-B0****
0.0033	13.0	9.0	4.0	10.0	0.6	HMMKP82/3A332-40****	0.15	32.0	20.0	11.0	27.5	0.8	HMMKP82/3A154-B0****
0.0039	13.0	11.0	5.0	10.0	0.6	HMMKP82/3A392-40****	0.18	32.0	22.0	13.0	27.5	0.8	HMMKP82/3A184-B0****
0.0047	13.0	11.0	5.0	10.0	0.6	HMMKP82/3A472-40****	0.22	32.0	22.0	13.0	27.5	0.8	HMMKP82/3A224-B0****
0.0056	13.0	12.0	6.0	10.0	0.6	HMMKP82/3A562-40****	0.27	32.0	24.5	15.0	27.5	0.8	HMMKP82/3A274-B0****
0.0068	13.0	12.0	0.6	10.0	0.6	HMMKP82/3A682-40****	0.33	32.0	28.0	14.0	27.5	0.8	HMMKP82/3A334-B0****
0.0082	18.0	11.0	5.0	15.0	0.8	HMMKP82/3A822-60****	0.39	32.0	33.0	18.0	27.5	0.8	HMMKP82/3A394-B0****
0.010	18.0	11.0	5.0	15.0	0.8	HMMKP82/3A103-60****	0.47	32.0	33.0	18.0	27.5	0.8	HMMKP82/3A474-B0****
0.012	18.0	11.0	5.0	15.0	0.8	HMMKP82/3A123-60****							
0.015	18.0	11.0	5.0	15.0	0.8	HMMKP82/3A153-60****							
0.018	18.0	12.0	6.0	15.0	0.8	HMMKP82/3A183-60****							
0.022	18.0	12.0	6.0	15.0	0.8	HMMKP82/3A223-60****							
0.027	18.0	13.0	7.0	15.0	0.8	HMMKP82/3A273-60****							
0.033	18.0	13.0	7.0	15.0	0.8	HMMKP82/3A333-60****							
0.039	18.0	14.5	8.5	15.0	0.8	HMMKP82/3A393-60****							

备注: (1)“-”表示容量等级, J=±5%, K=±10%, M=±20%。

(2)“****”表示引线加工和包装代码(见表1)。

产品尺寸

1600Vdc (650Vac)													
C _R (μF)	W mm	H mm	T mm	P mm	D mm	产品订货标记	C _R (μF)	W mm	H mm	T mm	P mm	D mm	产品订货标记
0.00068	18.0	11.0	5.0	15.0	0.8	HMMKP82/3C681-60****	0.015	26.0	15.0	6.0	22.5	0.8	HMMKP82/3C153-90****
0.00082	18.0	11.0	5.0	15.0	0.8	HMMKP82/3C821-60****	0.018	26.0	15.0	6.0	22.5	0.8	HMMKP82/3C183-90****
0.0010	18.0	11.0	5.0	15.0	0.8	HMMKP82/3C102-60****	0.022	26.0	15.0	6.0	22.5	0.8	HMMKP82/3C223-90****
0.0012	18.0	11.0	5.0	15.0	0.8	HMMKP82/3C122-60****	0.027	26.0	15.0	6.0	22.5	0.8	HMMKP82/3C273-90****
0.0015	18.0	11.0	5.0	15.0	0.8	HMMKP82/3C152-60****	0.033	26.0	16.0	7.0	22.5	0.8	HMMKP82/3C333-90****
0.0018	18.0	11.0	5.0	15.0	0.8	HMMKP82/3C182-60****	0.039	26.0	17.0	8.5	22.5	0.8	HMMKP82/3C393-90****
0.0022	18.0	11.0	5.0	15.0	0.8	HMMKP82/3C222-60****	0.047	26.0	17.0	8.5	22.5	0.8	HMMKP82/3C473-90****
0.0027	18.0	11.0	5.0	15.0	0.8	HMMKP82/3C272-60****	0.056	26.0	19.0	10.0	22.5	0.8	HMMKP82/3C563-90****
0.0033	18.0	11.0	5.0	15.0	0.8	HMMKP82/3C332-60****	0.068	26.0	20.0	11.0	22.5	0.8	HMMKP82/3C683-90****
0.0039	18.0	11.0	5.0	15.0	0.8	HMMKP82/3C392-60****	0.082	26.0	22.0	12.0	22.5	0.8	HMMKP82/3C823-90****
0.0047	18.0	11.0	5.0	15.0	0.8	HMMKP82/3C472-60****	0.10	26.0	22.0	12.0	22.5	0.8	HMMKP82/3C104-90****
0.0056	18.0	11.0	5.0	15.0	0.8	HMMKP82/3C562-60****	0.039	32.0	18.0	9.0	27.5	0.8	HMMKP82/3C393-B0****
0.0068	18.0	11	5.0	15.0	0.8	HMMKP82/3C682-60****	0.047	32.0	18.0	9.0	27.5	0.8	HMMKP82/3C473-B0****
0.0082	18.0	12.0	6.0	15.0	0.8	HMMKP82/3C822-60****	0.056	32.0	18.0	9.0	27.5	0.8	HMMKP82/3C563-B0****
0.010	18.0	12.0	6.0	15.0	0.8	HMMKP82/3C103-60****	0.068	32.0	18.0	9.0	27.5	0.8	HMMKP82/3C683-B0****
0.012	18.0	12.0	6.0	15.0	0.8	HMMKP82/3C123-60****	0.082	32.0	20.0	11.0	27.5	0.8	HMMKP82/3C823-B0****
0.015	18.0	13.5	7.5	15.0	0.8	HMMKP82/3C153-60****	0.10	32.0	20.0	11.0	27.5	0.8	HMMKP82/3C104-B0****
0.018	18.0	14.5	8.5	15.0	0.8	HMMKP82/3C183-60****	0.12	32.0	22.0	13.0	27.5	0.8	HMMKP82/3C124-B0****
0.022	18.0	14.5	8.5	15.0	0.8	HMMKP82/3C223-60****	0.15	32.0	28.0	14.0	27.5	0.8	HMMKP82/3C154-B0****
0.027	18.0	14.5	8.5	15.0	0.8	HMMKP82/3C273-60****	0.18	32.0	28.0	14.0	27.5	0.8	HMMKP82/3C184-B0****
0.033	18.0	16.0	10.0	15.0	0.8	HMMKP82/3C333-60****	0.22	32.0	28.0	17.0	27.5	0.8	HMMKP82/3C224-B0****
0.039	18.0	19.0	11.0	15.0	0.8	HMMKP82/3C393-60****	0.27	32.0	33.0	18.0	27.5	0.8	HMMKP82/3C274-B0****
0.047	18.0	19.0	11.0	15.0	0.8	HMMKP82/3C473-60****	0.33	32.0	33.0	18.0	27.5	0.8	HMMKP82/3C334-B0****
2000Vdc (700Vac)													
C _R (μF)	W mm	H mm	T mm	P mm	D mm	产品订货标记	C _R (μF)	W mm	H mm	T mm	P mm	D mm	产品订货标记
0.0010	18.0	11.0	5.0	15.0	0.8	HMMKP82/3D102-60****	0.0022	18.0	11.0	5.0	15.0	0.8	HMMKP82/3D222-60****
0.0012	18.0	11.0	5.0	15.0	0.8	HMMKP82/3D122-60****	0.0027	18.0	11.0	5.0	15.0	0.8	HMMKP82/3D272-60****
0.0015	18.0	11.0	5.0	15.0	0.8	HMMKP82/3D152-60****	0.0033	18.0	12.0	6.0	15.0	0.8	HMMKP82/3D332-60****
0.0018	18.0	11.0	5.0	15.0	0.8	HMMKP82/3D182-60****	0.0039	18.0	12.0	6.0	15.0	0.8	HMMKP82/3D392-60****

备注: (1)“-”表示容量等级, J=±5%, K=±10%, M=±20%。

(2)“****”表示引线加工和包装代码(见表1)。

产品尺寸

2000Vdc (700Vac)													
C _R (μF)	W mm	H mm	T mm	P mm	D mm	产品订货标记	C _R (μF)	W mm	H mm	T mm	P mm	D mm	产品订货标记
0.0047	18.0	12.0	6.0	15.0	0.8	HMMKP82/3D472-60****	0.022	26.0	17.0	8.5	22.5	0.8	HMMKP82/3D223-90****
0.0056	18.0	12.0	6.0	15.0	0.8	HMMKP82/3D562-60****	0.027	26.0	19.0	10.0	22.5	0.8	HMMKP82/3D273-90****
0.0068	18.0	13.0	7.0	15.0	0.8	HMMKP82/3D682-60****	0.033	26.0	19.0	10.0	22.5	0.8	HMMKP82/3D333-90****
0.0082	18.0	14.5	8.5	15.0	0.8	HMMKP82/3D822-60****	0.039	26.0	22.0	12.0	22.5	0.8	HMMKP82/3D393-90****
0.010	18.0	16.0	10.0	15.0	0.8	HMMKP82/3D103-60****	0.047	26.0	22.0	12.0	22.5	0.8	HMMKP82/3D473-90****
0.012	18.0	16.0	10.0	15.0	0.8	HMMKP82/3D123-60****	0.022	32.0	18.0	9.0	27.5	0.8	HMMKP82/3D223-B0****
0.015	18.0	19.0	11.0	15.0	0.8	HMMKP82/3D153-60****	0.027	32.0	18.0	9.0	27.5	0.8	HMMKP82/3D273-B0****
0.018	18.0	19.0	11.0	15.0	0.8	HMMKP82/3D183-60****	0.033	32.0	18.0	9.0	27.5	0.8	HMMKP82/3D333-B0****
0.0047	26.0	15.0	6.0	22.5	0.8	HMMKP82/3D472-90****	0.039	32.0	18.0	9.0	27.5	0.8	HMMKP82/3D393-B0****
0.0056	26.0	15.0	6.0	22.5	0.8	HMMKP82/3D562-90****	0.047	32.0	20.0	11.0	27.5	0.8	HMMKP82/3D473-B0****
0.0068	26.0	15.0	6.0	22.5	0.8	HMMKP82/3D682-90****	0.056	32.0	22.0	13.0	27.5	0.8	HMMKP82/3D563-B0****
0.0082	26.0	15.0	6.0	22.5	0.8	HMMKP82/3D822-90****	0.068	32.0	22.0	13.0	27.5	0.8	HMMKP82/3D683-B0****
0.010	26.0	15.0	6.0	22.5	0.8	HMMKP82/3D103-90****	0.082	32.0	28.0	14.0	27.5	0.8	HMMKP82/3D823-B0****
0.012	26.0	15.0	6.0	22.5	0.8	HMMKP82/3D123-90****	0.10	32.0	28.0	17.0	27.5	0.8	HMMKP82/3D104-B0****
0.015	26.0	15.0	6.0	22.5	0.8	HMMKP82/3D153-90****	0.12	32.0	33.0	18.0	27.5	0.8	HMMKP82/3D124-B0****
0.018	26.0	16.0	7.0	22.5	0.8	HMMKP82/3D183-90****	0.15	32.0	33.0	18.0	27.5	0.8	HMMKP82/3D154-B0****

备注: (1)"-"表示容量等级, J=±5%, K=±10%, M=±20%。

(2)****表示引线加工和包装代码(见表1)。