


FMD3N60E5
N-CHANNEL POWER MOSFET
Features :

- Fast body diode eliminates the need for external diode in ZVS applications.
- Lower Gate charge results in simpler drive requirements
- Higher Gate voltage threshold offers improved noise Immunity
- Low on-resistance
- RoHS compliant

Applications:

- Motor Control applications
- Uninterruptible Power Supplies
- Zero Voltage Switching SMPS

V_{DSS}	600	V
I_D	3	A
T_{rr}	85	ns
$R_{DS(ON)Typ}$	2.6	Ω


Absolute ($T_c = 25^\circ C$):

Symbol	Parameter	Rating	Units
V_{DSS}	Drain-to-Source Voltage	600	V
I_D	Continuous Drain Current	3*	A
	Continuous Drain Current $T_C = 100^\circ C$	1.95*	A
I_{DM} ①	Pulsed Drain Current	12*	A
V_{GS}	Gate-to-Source Voltage	± 30	V
E_{AS} ②	Single Pulse Avalanche Energy	157	mJ
E_{AR} ①	Avalanche Energy, Repetitive	15	mJ
I_{AR} ①	Avalanche Current	1.7	A
P_D	Power Dissipation	54	W
dv/dt	Peak Diode Recovery dv/dt	5	V/nS
T_J	Junction Temperature	150	$^\circ C$
T_{stg}	Storage Temperature Range	-55 to 150	$^\circ C$

*Drain current limited by maximum junction temperature

Ordering Information

Product number	Package	Marking	Packing	Quantity
FMD3N60E5	TO252T	FMD3N60E5	Tape & Reel	2500

Electronic Characteristics (Tc=25°C)

PARAMETER	SYMBOL	TEST CONDITION	MIN	TYP	MAX	UNIT
Drain-source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V, I_D=250\mu A$	600			V
Breakdown Voltage Temperature Coefficient	$\Delta BV_{DSS}/\Delta T_j$	$I_D=250\mu A$, Referenced to 25°C		0.6		V/°C
Gate Threshold Voltage	$V_{GS(TH)}$	$V_{GS}=V_{DS}, I_D=250\mu A$	2.0		4.0	V
Drain-source Leakage Current	I_{DSS}	$V_{DS}=600V, V_{GS}=0V, T_j=25^\circ C$			1	μA
		$V_{DS}=480V, V_{GS}=0V, T_j=125^\circ C$			100	μA
Forward Transconductance	g_{fs}	$V_{DS}=15V, I_D=1.5A$ ③		2.6		S
Gate-body Leakage Current	I_{GSS}	$V_{DS}=0V, V_{GS}=\pm 30V$			± 100	nA
Drain-source On Resistance	$R_{DS(ON)}$	$V_{GS}=10V, I_D=1.5A$ ③		2.6	3.2	Ω
Input Capacitance	C_{iss}	$V_{GS}=0V, V_{DS}=25V$ $F=1.0MHz$		430		pF
Output Capacitance	C_{oss}			42		
Reverse transfer Capacitance	C_{rss}			6		
Turn-on Delay Time	$T_{d(on)}$	$V_{DD}=300V, I_D=3.0A$ $R_G=25\Omega$ ③		10		ns
Rise Time	T_r			9		
Turn -Off Delay Time	$T_{d(off)}$			35		
Fall Time	T_f			10		
Total Gate Charge	Q_g	$I_D=3.0A, V_{DS}=480V$ $V_{GS}=10V$ ③		10.9		nC
Gate-to-Source Charge	Q_{gs}			3.4		nC
Gate-to-Drain Charge	Q_{gd}			1.7		nC
Continuous Diode Forward Current	I_s				3.0	A
Max Pulsed Diode Forward Current	I_{SM}				12	A
Diode Forward Voltage	V_{SD}	$T_j=25^\circ C, I_s=3.0A, V_{GS}=0V$ ③			1.4	V
Reverse Recovery Time	t_{rr}	$T_j=25^\circ C, I_f=3.0A$ $di/dt=100A/\mu s$ ③		84.6		ns
Reverse Recovery Charge	Q_{rr}				0.2	
Thermal Resistance Junction-case	R_{thJC}			2.31		°C/W
Thermal Resistance Junction-ambient	R_{thJA}			62.5		°C/W

Notes:

- ① Repetitive rating: Pulse width limited by maximum junction temperature
- ② Starting $T_j=25^\circ C, V_{DD}=50V, L=36mH, R_G=25\Omega, I_{AS}=3.0A$
- ③ Pulse Test : Pulse width $\leq 300\mu s$, Duty cycle $\leq 2\%$





 Fig1 Typical Output Characteristics, $T_c=25^\circ\text{C}$

 Fig2 Typical Output Characteristics, $T_c=150^\circ\text{C}$


Fig3 On-Resistance Vs. Temperature




Fig4 Typical Source-Drain Diode Forward Voltage




Fig5 Maximum Drain Current Vs. Case Temperature




Fig6 Maximum Safe Operating Area




Fig7 Gate Threshold Voltage Variation vs. Temperature




Fig8 Breakdown Voltage Variation vs. Temperature




Fig9 Capacitance Characteristics




Fig10 On-Resistance Variation VS. Drain Current and Gate Voltage





Fig11 Gate Charge VS Gate to Source Voltage


 Fig12 I_{DM} VS Pulse Width






Fig13 Normalized Thermal Impedance VS Rectangular Pulse Duration


TO-252T MECHANICAL DATA
UNIT: mm

SYMBOL	min	max	SYMBOL	min	max
A	2.20	2.40	B	0.85	1.25
b	0.50	0.80	C	0.45	0.70
b1	0.45	0.70	D	6.30	6.70
D1	5.10	5.50	E	5.30	6.20
L1	9.20	10.60	F	0.50	0.90
L2	0.90	1.50	e1	2.25	2.35
L3	0.60	1.10	e2	4.50	4.70
			K	0.00	0.18



TO-252T TAPE AND REEL DATA
UNIT: mm

SYMBOL	min	nom	max	SYMBOL	min	nom	max
A0	6.80	6.90	7.00	B0	10.40	10.50	10.60
K0	2.60	2.70	2.90	K1	2.40	2.50	2.60
F	7.40	7.50	7.60	K2	1.60	1.70	1.80
W	15.90	16.00	16.10	P1	7.90	8.00	8.10



Copyright Notice

Copyright by Fortior Technology (Shenzhen) Co., Ltd. All Rights Reserved.

Right to make changes —Fortior Technology (Shenzhen) Co., Ltd reserves the right to make changes in the products - including circuits, standard cells, and/or software - described or contained herein in order to improve design and/or performance. The information contained in this manual is provided for the general use by our customers. Our customers should be aware that the personal computer field is the subject of many patents. Our customers should ensure that they take appropriate action so that their use of our products does not infringe upon any patents. It is the policy of Fortior Technology (Shenzhen) Co., Ltd. to respect the valid patent rights of third parties and not to infringe upon or assist others to infringe upon such rights.

This manual is copyrighted by Fortior Technology (Shenzhen) Co., Ltd. You may not reproduce, transmit, transcribe, store in a retrieval system, or translate into any language, in any form or by any means, electronic, mechanical, magnetic, optical, chemical, manual, or otherwise, any part of this publication without the expressly written permission from Fortior Technology (Shenzhen) Co., Ltd.

Fortior Technology(Shenzhen) Co.,Ltd.

Room203,2/F, Building No.11,Keji Central Road2,
SoftwarePark, High-Tech Industrial Park, Shenzhen, P.R. China 518057
Tel: 0755-26867710
Fax: 0755-26867715
URL: <http://www.fortiortech.com>

Contained herein

Copyright by Fortior Technology (Shenzhen) Co.,Ltd all rights reserved.